WHAT IS CLAIMED IS:

- 1. A method of accommodating code collisions from multiple
- 2 SAW identification tag coded response pulses, comprising:
- 3 separating probable candidates by time-domain;
- 4 classifying said probable candidates by code-division
- 5 separation;
- 6 employing known coded identification signals to adjust said
- 7 probable candidates; and
- 8 correlating said multiple SAW identification tag coded
- 9 response pulses to identify said probable candidates for further
- 10 processing.
- The method as described in Claim 1 further comprising
 focusing an interrogation pulse to within a defined space.
- 3. The method as described in Claim 1 wherein said
- 2 correlating is further comprised of storing said multiple SAW
- 3 identification tag coded response pulses in a database for further
- 4 processing.
- 4. The method as described in Claim 1 wherein said
- 2 correlating is further comprised of filtering said multiple SAW
- 3 identification tag coded response pulses for matching signals.

- 5. The method as described in Claim 1 further comprising subtracting certain known coded identification signals from said probable candidates.
- 6. The method as described in Claim 1 wherein said known coded identification signals include known signal templates.
- 7. The method as described in Claim 1 wherein said time2 domain is based on a hierarchical order.
- 8. The method as described in Claim 7 wherein said
 hierarchical order is from a general object classification to a
 specific object included within said general object classification.
- 9. The method as described in Claim 1 further comprising error-checking said SAW identification tag coded response pulses.
- 10. The method as described in Claim 1 wherein said separating, classifying, employing, and correlating are in a predetermined sequence.

- 11. A method of identifying a unique SAW identification tag

 coded response pulse for further processing from among multiple SAW

 identification tag coded response pulses, comprising:
- separate said multiple SAW identification tag coded response pulses by time-domain to identify probable candidates;
- 6 classify said probable candidates by code-division;
- employ known coded identification signals to adjust said probable candidates; and
- correlate said multiple SAW identification tag coded response pulses to identify said probable candidates for further processing.
 - 12. The method as described in Claim 11 further comprising focusing an interrogation pulse to within a defined space.
- 13. The method as described in Claim 11 wherein said

 correlate is further comprised of storing said multiple SAW

 identification tag coded response pulses in a database for further processing.
- 14. The method as described in Claim 11 wherein said correlate is further comprised of filtering said multiple SAW identification tag coded response pulses for matching signals.

- 15. The method as described in Claim 11 further comprising subtracting said known coded identification signals from said probable candidates.
- 16. The method as described in Claim 11 wherein said known coded identification signals include a known signal templates.
- 17. The method as described in Claim 11 wherein said timedomain is based on a hierarchical order.
- 18. The method as described in Claim 17 wherein said hierarchical order is from a general object classification to a specific object within said general object classification.
- 19. The method as described in Claim 11 further comprising error-checking said SAW identification tag coded response pulses.
- 20. The method as described in Claim 11 wherein said separate, classify, employ and correlate are in a pre-determined sequence.